

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)

ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION

(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICIÓN.)

API 598 - VALVE INSPECTION AND TESTING API 599 - METAL PLUG VALVES - FLANGED, THREADED AND WELDING ANSI B16-10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES ANSI B16-34 - VALVES - FLANGED, THREADED AND WELDING ENDS MSS-SP61 - PRESSURE TESTING OF STEEL VALVES	API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK API 600 - STEEL GATE VALVES, FLANGED AND WELDING ENDS ANSI B16-11 - FORGED FITTINGS, SOCKET - WELDING AND THREADED API 602 - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS
---	---

Part No. AC061A08MAB830000Z
 (Código) **6" Fig. 5202 F UT WCB, API TRIM No.8 830000**
Description
 Descripción **CAST STEEL GATE VALVE 150 CLASS**
(VALVULA COMPUERTA DE ACERO FUNDIDO CLASE 150)

VALVE WITH LOW EMISSION CONTROL (50 PPM'S MAX.) (VALVULA SUMINISTRADA CON CONTROL DE BAJAS EMISIONES FUGITIVAS (50 PPM'S MAX.))

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSD) (HIDROSTATICA)	450	450	NA	NA
PNEUMATIC (PSD) (NEUMATICA)			80	80

MECHANICAL TESTS (PROP. MECANICAS)

CHEMICAL COMPOSITION (%)													COMPOSICIÓN QUIMICA (%)					TENS	YIELD	ELG	RED	BHN
ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	KPSI CVN@	KPSI 1ST	% 2ND	% 3RD	AVG				
BODY CUERPO	K0499	ASTM A-216/WCB	0.217	0.934	0.034	0.030	0.547	0.014	0.026	0.103	0.023	0.011		74.24	45.24	22	41	154				
BONNET BONETE	K0462	ASTM A-216/WCB	Normalized (Normalizado a) 930 °C Temper to (Temple a) 650 °C										Air Cooled. (Enfriado en aire.)									
WEDGE DISCO	K0524	ASTM A-216/WCB	0.185	0.950	0.035	0.033	0.421	0.009	0.024	0.012	0.020	0.009		75.69	44.95	25	39	154				
			Normalized (Normalizado a) 930 °C Temper to (Temple a) 650 °C										Air Cooled. (Enfriado en aire.)									
			0.187	0.923	0.024	0.018	0.479	0.032	0.016	0.016	0.023	0.013		74.24	46.11	26	36	153				
			Normalized (Normalizado a) 930 °C Temper to (Temple a) 650 °C										Air Cooled. (Enfriado en aire.)									

 CERTIFICADO POR:
 ASEGURAMIENTO DE CALIDAD

 CERTIFIED BY :
 QUALITY ASSURANCE


Jessica Garcia