



Industrial de Valvulas, S.A. de C.V.  
 Av. de La Industria Lote 16 Fracc. Industrial El Trebol  
 Tepotzotlan, Estado de Mexico C.P. 54600

(Numero) Number  
 (Fecha) Date

V11C8363  
 12/04/2011

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)

### ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION:

(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICIÓN.)

API 598  
 API 599  
 ANSI B16-10  
 ANSI B16-34  
 MSS-SP61

- VALVE INSPECTION AND TESTING  
 - METAL PLUG VALVES - FLANGED, THREADED AND WELDING  
 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES  
 - VALVES - FLANGED, THREADED AND WELDING ENDS  
 - PRESSURE TESTING OF STEEL VALVES

API 6D  
 API 600  
 ANSI B16-11  
 API 602

- PIPELINE VALVES - GATE, PLUG, BALL AND CHECK  
 - STEEL GATE VALVES, FLANGED AND WELDING ENDS  
 - FORGED FITTINGS, SOCKET - WELDING AND THREADED  
 - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS

Part No. **AC041A08MAA8300000**  
 (Código)  
 Description **4" Fig. 5202 F UT WCB, API TRIM No.8 830000**  
 Descripción **CAST STEEL GATE VALVE 150 CLASS**  
**(VALVULA COMPUERTA DE ACERO FUNDIDO CLASE 150)**

VALVE WITH LOW EMISSION CONTROL (50 PPM'S MAX.) (VALVULA SUMINISTRADA CON CONTROL DE BAJAS EMISIONES FUGITIVAS (50 PPM'S MAX.))

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	450	450	NA	NA
PNEUMATIC (PSI) (NEUMATICA)			80	80

#### MECHANICAL TESTS (PROP. MECANICAS)

CHEMICAL COMPOSITION (%)													COMPOSICIÓN QUIMICA (%)					TENS	YIELD	ELG	RED	BHN
ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	KPSI CVN@	KPSI 1ST	% 2ND	% 3RD	AVG				
BODY CUERPO	WH23661	ASTM A-216/WCB	0.217	0.896	0.029	0.017	0.449	0.006	0.017	0.019	0.045	0.005		77.43	47.56	30	58	154				
BONNET BONETE	XS316	ASTM A-216/WCB	0.220	0.580	0.020	0.021	0.220	0.070	0.039	0.090	0.000	0.000		71.77	42.77	24	40	170				
WEDGE DISCO	D3859	ASTM A-217/CA15	0.100	0.770	0.030	0.014	1.080	0.890	12.270	0.011	0.041	0.002		99.90	70.61	25	47	272				
			Normalizated to (Normalizado a) 930				Temper to (Temple a) 650				Cooled in air. (Enfriado en aire.)											
			Normalizado a (Normalizado to) 970				Temple a (Temper to) 630				Cooled in air. (Enfriado en aire.)											

Jessica Garcia

CERTIFICADO POR:  
 ASEGURAMIENTO DE CALIDAD

CERTIFIED BY:  
 QUALITY ASSURANCE