

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)  
**ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO**

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION:

(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICIÓN.)

- |             |   |
|-------------|---|
| API 598     | - VALVE INSPECTION AND TESTING                      |
| API 599     | - METAL PLUG VALVES - FLANGED, THREADED AND WELDING |
| ANSI B16-10 | - FACE TO FACE AND END TO END DIMENSIONS OF VALVES  |
| ANSI B16-34 | - VALVES - FLANGED, THREADED AND WELDING ENDS       |
| MSS-SP61    | - PRESSURE TESTING OF STEEL VALVES                  |

- |             |   |
|-------------|---|
| API 6D      | - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK                                    |
| API 600     | - STEEL GATE VALVES, FLANGED AND WELDING ENDS                                     |
| ANSI B16-11 | - FORGED FITTINGS, SOCKET - WELDING AND THREADED                                  |
| API 602     | - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS |

**Part No. AC011A08MAA8300000**  
 (Código)  
**Description 2" Fig. 5202 F UT WCB, API TRIM No.8 830000**  
 Descripción CAST STEEL GATE VALVE 150 CLASS  
 (VALVULA COMPUERTA DE ACERO FUNDIDO CLASE 150)

VALVE WITH LOW EMISSION CONTROL (50 PPM'S MAX.) (VALVULA SUMINISTRADA CON CONTROL DE BAJAS EMISIONES FUGITIVAS (50 PPM'S MAX.) )


PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	450	450	N A	N A
PNEUMATIC (PSI) (NEUMATICA)			80	80

### MECHANICAL TESTS (PROP. MECANICAS)

CHEMICAL COMPOSITION (%)			COMPOSICIÓN QUIMICA (%)										MECHANICAL TESTS (PROP. MECANICAS)					
ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	TENS KPSI CVN@	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD	BHN AVG
BODY CUERPO	WH19576	ASTM A-216/WCB	0.200	0.896	0.014	0.007	0.408	0.040	0.069	0.025	0.020	0.004		72.07	37.27	34	54	158
Normalized to (Normalizado a) 930			Temper to (Temple a) 650										Cooled in air. (Enfriado en aire.)					
BONNET BONETE	WH21280	ASTM A-216/WCB	0.191	0.960	0.012	0.012	0.537	0.053	0.040	0.026	0.018	0.006		79.02	46.40	27	56	154
Normalized to (Normalizado a) 920			Temper to (Temple a) 650										Cooled in air. (Enfriado en aire.)					
WEDGE DISCO	WH81745	ASTM A-217/CA15	0.142	0.624	0.024	0.013	0.711	0.120	13.780	0.017	0.010	0.026		98.31	71.34	24	42	300
Normalized a (Normalizado to) 970			Temple a (Temper to) 630										Enfriado en aire. (Cooled in air.)					

 CERTIFICADO POR:  
 ASEGURAMIENTO DE CALIDAD

 CERTIFIED BY:  
 QUALITY ASSURANCE

  
 \_\_\_\_\_  
 Jessica García