

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)  
**ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO**

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION

(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICIÓN.)

- |  |   |
|--|---|
| API 598 - VALVE INSPECTION AND TESTING<br>API 599 - METAL PLUG VALVES- FLANGED, THREADED AND WELDING<br>ANSI B16-10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES<br>ANSI B16-34 - VALVES - FLANGED, THREADED AND WELDING ENDS<br>MSS-SP61 - PRESSURE TESTING OF STEEL VALVES | API 6D - PIPELINE VALVES- GATE, PLUG, BALL AND CHECK<br>API 600 - STEEL GATE VALVES, FLANGED AND WELDING ENDS<br>ANSI B16-11 - FORGED FITTINGS, SOCKET- WELDING AND THREADED<br>API 602 - COMPACT STEEL GATE VALVES- FLANGED, THREADED, WELDING AND EXTENDED- BODY ENDS |
|--|---|

**Part No. AC041A08MAB830000F**  
 (Código) **4" Fig. 5202 F UT WCB, API TRIM No.8 830000**

**Description** CAST STEEL GATE VALVE 150 CLASS  
 Descripción (VALVULA COMPUERTA DE ACERO FUNDIDO CLASE 150)

VALVE WITH LOW EMISSION CONTROL (50 PPM'S MAX.) (VALVULA SUMINISTRADA CON CONTROL DE BAJAS EMISIONES FUGITIVAS (50 PPM'S MAX.))

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	450	450	N A	N A
PNEUMATIC (PSI) (NEUMATICA)			80	80

**MECHANICAL TESTS (PROP. MECANICAS)**

CHEMICAL COMPOSITION (%)			COMPOSICIÓN QUIMICA (%)											MECHANICAL TESTS (PROP. MECANICAS)				
ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	TENS KPSI CVN@	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD	BHN AVG
BODY CUERPO	N1886	ASTM A-216/WCB	0.218	0.715	0.021	0.021	0.412	0.033	0.144	0.151	0.044	0.016		74.68	43.50	25	39	162
			Normalized (Normalizado a) 930 °C Temper to (Temple a) 650 °C Air Cooled. (Enfriado en aire.)															
BONNET BONETE	N2265	ASTM A-216/WCB	0.212	0.702	0.018	0.020	0.410	0.030	0.150	0.150	0.040			74.68	45.68	25	41	158
			Normalized (Normalizado a) 930 °C Temper to (Temple a) 650 °C Air Cooled. (Enfriado en aire.)															
WEDGE DISCO	357	ASTM A-216/WCB	0.220	0.840	0.026	0.020	0.470	0.080	0.060	0.010	0.050	0.000		74.53	46.11	29	49	148
			Air Cooled. (Enfriado en aire.)															

CERTIFICADO POR: ASEGURAMIENTO DE CALIDAD  
 CERTIFIED BY: QUALITY ASSURANCE

  
 \_\_\_\_\_  
**Jessica García**