



Industrial de Válvulas, S.A. de C.V.

Industria Ite 16 S/N Fracc. Industrial el Trébol de Tepetztlán, Estado de México, México C.P. 54610

**CERTIFICATE OF MATERIALS & TEST REPORT (CMTR)**  
(CERTIFICADO DE CALIDAD DE MATERIALES Y REPORTE DE PRUEBAS CMTR)  
ACCORDING TO EN 10204 TYPE 3.1

No. código interno (Product Code Nr.): **AR030BA08MANA1BG**

No. Serie (Serial Number): **V148R1955**

Fecha (Date): **March 15, 2016**

No. De Tag (Tag Number):

Clientes (Customer):

No Pedido del Cliente (Customer PO Nr.):

Partida (Customer Item): **Pedido Interno No (Walworth Sales Nr.):**

Partida (Item):

Linea de producto (Product line):	CAST STEEL	Extremos (Ends):	RAISED FACE (RF TYPE "A")	Operación (Operation):	N/A
Tipo de válvula (Type of valve):	SWING CHECK	Cuerpo (Shell):	WCB	Otros (Other requirements):	
Diámetro (Nominal diameter):	3	Interiores (Trim):	#08 (UT)		
Presión clase (Pressure class):	150	Figura No (Figure Nr.):	FIG 5341		

**COMPOSICION QUIMICA EN % (CHEMICAL COMPOSITION %)**


Parte (Component)	Material (Material)	Colada (Heat)	% C	% Mn	% P	% S	% Si	% Ni	% Cr	% Mo	% Cu	% V	%	%	%	%	%	%
CUERPO (BODY)	ASTM_A_216_GR_WCB	K4H86	0.203	0.725	0.025	0.026	0.443	0.036	0.055	0.015	0.068	0.001	0.000	0.000	0.000	0.000	0.000	0.000
DISCO 1 (DISC 1)	ASTM_A_216_GR_WCB	FH86	0.214	0.964	0.022	0.028	0.353	0.040	0.080	0.012	0.029	0.001	0.000	0.000	0.000	0.000	0.000	0.000
TAPA 1 (CAP 1)	ASTM_A_216_GR_WCB	K4H78	0.183	0.777	0.025	0.029	0.420	0.041	0.036	0.020	0.060	0.001	0.000	0.000	0.000	0.000	0.000	0.000

**PROPIEDADES MECANICAS (MECHANICAL TESTING)**

Parte (Component)	Colada (Heat)	Condición de TT Normalizado & revenido Heat Treatment condition (Normalized & tempered)	Cedencia (Tensile strength) (Kpsi)	Tensión (Yield strength) (Kpsi)	Alar. En 2" (Elong. In 2") (% min)	Reduccion de area (Reduction of area) (% min)	Dureza (Hardness) (Bhn)		Prueba Impacto (Impact Test) (Joules)				
							1st	2nd	1st	2nd	3rd	AVG	
CUERPO (BODY)	K4H86	(910-940) °C, NORMALIZADO ( RECOCIDO ) 650 °C ENFRIAMIENTO CON AIRE (910-940) °C, NORMALIZE ( ANNEAL ) 650 °C AIR COOL	45.3900	76.1300	30	42	151	0	0	0	0	0	0
DISCO 1 (DISC 1)	FH86	(910-940) °C, NORMALIZADO ( RECOCIDO ) 650 °C ENFRIAMIENTO CON AIRE (910-940) °C, NORMALIZE ( ANNEAL ) 650 °C AIR COOL	46.1100	74.5300	37	60	154	0	0	0	0	0	0
TAPA 1 (CAP 1)	K4H78	(910-940) °C, NORMALIZADO ( RECOCIDO ) 650 °C ENFRIAMIENTO CON AIRE (910-940) °C, NORMALIZE ( ANNEAL ) 650 °C AIR COOL	46.2550	92.3650	28	58	156	0	0	0	0	0	0

**PRUEBAS DE PRESIÓN DE ACUERDO CON API 6D (PRESSURE TEST IN ACCORDANCE WITH API 6D)**

TIPO DE PRUEBA (Type of test)	PRESION (Pressure) (Psi)	TIEMPO (Duration) (min)	RESULTADO (Result)	TIPO DE PRUEBA (Type of test)	RESULTADO (Result)
HIDROSTATICA DE CASCO (HYDROSTATIC SHELL)	450	2 min	ACEPTADO (ACCEPTED)		
PRUEBA HIDROSTATICA SELLO 1 (HIGH PRESSURE CLOSURE SIDE 1)	315	2 min	ACEPTADO (ACCEPTED)		



Certificamos que este producto ha sido diseñado, fabricado y probado de acuerdo con nuestro sistema de administración de calidad y con los requisitos establecidos en una o más de las siguientes normas en su última edición. (We hereby certify this product has been designed, manufactured and tested according to our quality management system and requirements stated in one or more of the following standards on their latest edition).

DESIGN IN ACCORDANCE WITH ASME B16.34 (CAST STEEL SWING CHECK)  
API 599 METAL PLUG VALVES—FLANGED THREADED AND WELDING  
API 591 PROCESS VALVE QUALIFICATION PROCEDURE  
API 603 STEEL GLOBE VALVES—FLANGED AND BUTT WELDING ENDS, BOLTED BODIES  
API 604 TYPE TESTING OF RIGID STEM VALVES EQUIPPED WITH GRAPHITE PACKING FOR FUGITIVE EMISSIONS  
ANSI B16-10 FACE TO FACE AND END TO END DIMENSIONS OF VALVES  
ANSI B16-11 FORGED FITTINGS, SOCKETS—WELDING AND THREADED  
ANSI/NACE MR0175/ISO 15156-1 MATERIALS FOR USE IN H<sub>2</sub>S-CONTAINING ENVIRONMENTS IN OIL AND GAS PRODUCTION  
NACE MR0175 MATERIAL RESISTANT TO SULFIDE STRESS CRACKING IN CORROSIVE PETROLEUM ENVIRONMENT  
MSS-SP-11 PRESSURE TESTING OF STEEL VALVES

Quality Assurance Department

FAC-24 Rev. Original.