

No. código interno (Product Code Nr.): **AC160BA08MA2A1XR**

 No. Serie (Serial Number): **V17NC4026**

 Fecha (Date): **May 25, 2018**

No. De Tag (Tag Number):

 Clientes (Customer): **PLESA ANAHUAC Y CIAS, S.A DE C.V.**

 No Pedido del Cliente (Customer PO Nr.): **26809**

 Partida (Customer Item): **3** Pedido Interno No (Walworth Sales Nr.): **D000080251**

 Partida (Item): **3**

Linea de producto (Product line):	Cast Steel / Acero Fundido	Extremos (Ends):	RF	Operación (Operation):	Handwheel
Tipo de válvula (Type of valve):	Gate / Compuerta	Cuerpo (Body):	WCB	Anexo No. (Annex Nr.):	000000
Diámetro (Nominal diameter):	16	Interiores (Trim):	#08 ((API); (UT))	Otros (Other requirements):	
Presión clase (Pressure class):	150	Figura No (Figure Nr.):	FIG 5202RF		

COMPOSICION QUIMICA EN % (CHEMICAL COMPOSITION %)

Parte (Component)	Material (Material)	Colada (Heat)	% C	% Mn	% P	% S	% Si	% Ni	% Cr	% Mo	% Cu	% V	%	%	%	%	%	%
BONETE (BONNET)	ASTM_A_216_GR_WCB	E2008	0.210	0.850	0.027	0.019	0.410	0.017	0.057	0.019	0.040	0.003	0.000	0.000	0.000	0.000	0.000	0.000
CUERPO (BODY)	ASTM_A_216_GR_WCB	E2008	0.210	0.850	0.027	0.019	0.410	0.017	0.057	0.019	0.040	0.003	0.000	0.000	0.000	0.000	0.000	0.000
DISCO 1 (DISC 1)	ASTM_A_216_GR_WCB	E0216	0.190	0.660	0.027	0.010	0.360	0.035	0.054	0.007	0.033	0.007	0.000	0.000	0.000	0.000	0.000	0.000

PROPIEDADES MECANICAS (MECHANICAL TESTING)

Parte (Component)	Colada (Heat)	Condición de TT Normalizado & revenido Heat Treatment condition (Normalized & tempered)	Cedencia (Yield strength) (Kpsi)	Tensión (Tensile strength) (Kpsi)	Alar. En 2" (Elong. In 2") (% min)	Reduccion de area (Reduction of area) (% min)	Dureza (Hardness) (Bhn)		Prueba Impacto (Impact Test) (Joules)				
							1st	2nd	1st	2nd	3rd	AVG	
BONETE (BONNET)	E2008	(910-940) °C, NORMALIZADO (RECOCIDO) 650 °C ENFRIAMIENTO CON AIRE (910-940) °C, NORMALIZE (ANNEAL) 650 °C AIR COOL	44.5150	73.2250	29	50	153	0	0	0	0	0	0
CUERPO (BODY)	E2008	(910-940) °C, NORMALIZADO (RECOCIDO) 650 °C ENFRIAMIENTO CON AIRE (910-940) °C, NORMALIZE (ANNEAL) 650 °C AIR COOL	44.5150	73.2250	29	50	153	0	0	0	0	0	0
DISCO 1 (DISC 1)	E0216	(910-940) °C, NORMALIZADO (RECOCIDO) 650 °C ENFRIAMIENTO CON AIRE (910-940) °C, NORMALIZE (ANNEAL) 650 °C AIR COOL	43.0000	72.0000	31	56	166	0	0	0	0	0	0

PRUEBAS DE PRESIÓN DE ACUERDO CON API 598 (PRESSURE TEST IN ACCORDANCE WITH API 598)

TIPO DE PRUEBA (Type of test)	PRESION (Pressure) (Psi)	TIEMPO (Duration) (min)	RESULTADO (Result)	TIPO DE PRUEBA (Type of test)	RESULTADO (Result)
HIDROSTATICA DE CASCO (HYDROSTATIC SHELL)	450	5 min	ACEPTADO (ACCEPTED)		
HIDROSTATICA DE CASQUILLO (HYDROSTATIC BACK SEAT)	450	5 min	ACEPTADO (ACCEPTED)		
PRUEBA NEUMATICA SELLO 1 (LOW PRESSURE SIDE 1)	80	2 min	ACEPTADO (ACCEPTED)		
PRUEBA NEUMATICA SELLO 2 (LOW PRESSURE SIDE 2)	80	2 min	ACEPTADO (ACCEPTED)		

Certificamos que este producto ha sido diseñado, fabricado y probado de acuerdo con nuestro sistema de administración de calidad y con los requisitos establecidos en una o más de las siguientes normas en su última edición. (We hereby certify this product has been designed, manufactured and tested according to our quality management system and requirements stated in one or more of the following standards on their latest edition).

DESIGN AND TEST IN ACCORDANCE WITH:
 API 598- VALVE INSPECTION AND TESTING
 API 600- STEEL GATE VALVES-FLANGED AND BUTT-WELDING ENDS, BOLTED BONNETS



Quality Assurance Department
 Yolanda Ponciano Montoya
 FAC-24 Rev. Original.