

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)

ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION:

(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICIÓN.)

- | | | | |
|-------------|---|-------------|---|
| API 598 | - VALVE INSPECTION AND TESTING | API 6D | - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK |
| API 599 | - METAL PLUG VALVES - FLANGED, THREADED AND WELDING | API 600 | - STEEL GATE VALVES, FLANGED AND WELDING ENDS |
| ANSI B16-10 | - FACE TO FACE AND END TO END DIMENSIONS OF VALVES | ANSI B16-11 | - FORGED FITTINGS, SOCKET - WELDING AND THREADED |
| ANSI B16-34 | - VALVES - FLANGED, THREADED AND WELDING ENDS | API 602 | - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS |
| MSS-SP61 | - PRESSURE TESTING OF STEEL VALVES | | |

Part No. **BCSB056E08AAB830000C**

(Código)

1/2" Fig. 950 S UT A105, API TRIM No.8 830000

Description
Descripción

**FORGED STEEL GATE VALVE CLASS 800
(VALVULA COMPUERTA DE ACERO FORJADO CLASE 800)**

VALVE WITH LOW EMISSION CONTROL (50 PPM'S MAX.) (VALVULA SUMINISTRADA CON CONTROL DE BAJAS EMISIONES FUGITIVAS (50 PPM'S MAX.))

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	2975	2975	N A	N A
PNEUMATIC (PSI) (NEUMATICA)			80	80

Invoice(Factura) A4001 Item(Partida) 2
Qty(Cantidad) 200

MECHANICAL TESTS (PROP. MECANICAS)

CHEMICAL COMPOSITION (%)

COMPOSICIÓN QUIMICA (%)


TENS YIELD ELG RED BHN

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	KPSI CVN@	KPSI 1ST	% 2ND	% 3RD	AVG
BODY CUERPO	BBZ	ASTM A-105N	0.200	0.770	0.016	0.011	0.240	0.010	0.060	0.070	0.040	0.031		71.05	47.13	33	43	159
BODY CUERPO	CCN	ASTM A-105N	0.230	0.800	0.020	0.007	0.200	0.050	0.030	0.020	0.050	0.010		78.30	52.20	36	55	170
BODY CUERPO	CAY	ASTM A-105N	0.200	0.760	0.019	0.005	0.230	0.040	0.080	0.040	0.170	0.030		76.12	53.65	31	74	160
YOKE YUGO	BCD	ASTM A-105N	0.190	0.800	0.021	0.006	0.220	0.010	0.060	0.070	0.040	0.030		73.23	47.13	32	43	153
YOKE YUGO	BCF	ASTM A-105N	0.200	0.920	0.011	0.009	0.220	0.052	0.110	0.055	0.050	0.021		78.30	54.38	33	52	160
YOKE YUGO	CCN	ASTM A-105N	0.230	0.800	0.020	0.007	0.200	0.050	0.030	0.020	0.050	0.010		78.30	52.20	36	55	170

FAC10-21 REV "3"

CERTIFICADO POR:
ASEGURAMIENTO DE CALIDAD

CERTIFIED BY :
QUALITY ASSURANCE


Jessica Garcia