

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)

### ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION:

(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICIÓN.)

API 598 - VALVE INSPECTION AND TESTING  
API 599 - METAL PLUG VALVES - FLANGED, THREADED AND WELDING  
ANSI B16-10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES  
ANSI B16-34 - VALVES - FLANGED, THREADED AND WELDING ENDS  
MSS-SP61 - PRESSURE TESTING OF STEEL VALVES

API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK  
API 600 - STEEL GATE VALVES, FLANGED AND WELDING ENDS  
ANSI B16-11 - FORGED FITTINGS, SOCKET - WELDING AND THREADED  
API 602 - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS

Part No. **BCSB206F08AAB790000G**  
(Código)  
Description **2" Fig. 950 SW UT A105N, API TRIM No.8 790000**  
Descripción **FORGED STEEL GATE VALVE CLASS 800**  
**(VALVULA COMPUERTA DE ACERO FORJADO CLASE 800)**

VALVE MANUFACTURED TO MEET LOW FUGITIVE EMISSION (50 PPM'S MAX) & NACE SERVICE MR-01-75 (VALVULA SUMINISTRADA CON CONTROL DE BAJAS EMISIONES FUGITIVAS 50 PPM'S MAX.) Y PARA SERVICIO NACE MR-01-75 / MR0103-2007)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	2975	2175	N A	N A
PNEUMATIC (PSI) (NEUMATICA)			80	80

Invoice(Factura) A17188 Item(Partida) 1  
Qty(Cantidad) 24

#### MECHANICAL TESTS (PROP. MECANICAS)

#### CHEMICAL COMPOSITION (%)

#### COMPOSICIÓN QUIMICA (%)

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%)										MECHANICAL TESTS (PROP. MECANICAS)				
			C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	TENS KPSI CVN@	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD
BODY CUERPO	D37	ASTM A-105N	0.190	0.760	0.019	0.017	0.250	0.082	0.077	0.063	0.074	0.001	75.84	40.75	32	39	156
BODY CUERPO	D35	ASTM A-105N	0.180	0.750	0.022	0.020	0.260	0.083	0.082	0.053	0.068	0.001	76.27	41.33	34	40	158
BODY CUERPO	D38	ASTM A-105N	0.210	0.710	0.022	0.019	0.310	0.057	0.061	0.056	0.073	0.001	74.82	39.73	28	37	155
YOKE YUGO	D37	ASTM A-105N	0.190	0.760	0.019	0.017	0.250	0.082	0.077	0.063	0.074	0.001	75.84	40.75	32	39	156
YOKE YUGO	D35	ASTM A-105N	0.180	0.750	0.022	0.020	0.260	0.083	0.082	0.053	0.068	0.001	76.27	41.33	34	40	158
YOKE YUGO	D36	ASTM A-105N	0.191	0.792	0.020	0.019	0.220	0.068	0.083	0.059	0.082	0.001	77.14	40.60	39	44	158