

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)

### ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION:

(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICIÓN.)

API 598 API 599 ANSI B16-10 ANSI B16-34 MSS-SP61	- VALVE INSPECTION AND TESTING - METAL PLUG VALVES - FLANGED, THREADED AND WELDING - FACE TO FACE AND END TO END DIMENSIONS OF VALVES - VALVES - FLANGED, THREADED AND WELDING ENDS - PRESSURE TESTING OF STEEL VALVES	API 6D API 600 ANSI B16-11 API 602	- PIPELINE VALVES - GATE, PLUG, BALL AND CHECK - STEEL GATE VALVES, FLANGED AND WELDING ENDS - FORGED FITTINGS, SOCKET - WELDING AND THREADED - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS
--	--	---	--

**Part No. BGSB056F08AAB830000C**

(Código)

**1/2" Fig. 5520 SW UT A105N, API TRIM No.8 830000**

**Description**  
 Descripción

**FORGED STEEL GLOBE VALVE CLASS 800**  
**(VALVULA GLOBO DE ACERO FORJADO CLASE 800)**

VALVE WITH LOW EMISSION CONTROL (50 PPM'S MAX.) (VALVULA SUMINISTRADA CON CONTROL DE BAJAS EMISIONES FUGITIVAS (50 PPM'S MAX.))

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSD) (HIDROSTATICA)	2975	2975	2175	N A
PNEUMATIC (PSD) (NEUMATICA)			80	N A


**Invoice(Factura) A6450 Item(Partida) 4**  
**Qty(Cantidad) 20**

**MECHANICAL TESTS (PROP. MECANICAS)**

**CHEMICAL COMPOSITION (%)**

**COMPOSICIÓN QUIMICA (%)**

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%)										TENS	YIELD	ELG	RED	BHN
			C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	KPSI CVN@	KPSI 1ST	% 2ND	% 3RD
BODY CUERPO	CCL	ASTM A-105N	0.220	0.750	0.021	0.006	0.270	0.030	0.040	0.028	0.140	0.025	74.68	54.38	32	55	170
BODY CUERPO	CAX	ASTM A-105N	0.220	0.720	0.022	0.008	0.270	0.050	0.030	0.030	0.030	0.021	79.32	52.92	35	54	170
YOKE YUGO	CCL	ASTM A-105N	0.220	0.750	0.021	0.006	0.270	0.030	0.040	0.028	0.140	0.025	74.68	54.38	32	55	170



CERTIFICADO POR:  
 ASEGURAMIENTO DE CALIDAD

CERTIFIED BY :  
 QUALITY ASSURANCE

**Jessica García**