



Industrial de Valvulas, S.A. de C.V.  
 Av. de La Industria Lote 16 Fracc. Industrial El Trebol  
 Tepozotlan, Estado de México C.P. 54600  
 Teléfono: (52 55) 5899 1700 Fax: (52 55) 5876 0156  
 E-Mail: info@walworth.com.mx Web: www.walworthvalves.com

(Numero) Number  
 (Fecha) Date

3708/2013  
 22/10/2013

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)

### ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION:

(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICIÓN.)

- API 598 - VALVE INSPECTION AND TESTING
- API 599 - METAL PLUG VALVES - FLANGED, THREADED AND WELDING
- ANSI B16-10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- ANSI B16-34 - VALVES - FLANGED, THREADED AND WELDING ENDS
- MSS-SP61 - PRESSURE TESTING OF STEEL VALVES

- API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
- API 600 - STEEL GATE VALVES, FLANGED AND WELDING ENDS
- ANSI B16-11 - FORGED FITTINGS, SOCKET - WELDING AND THREADED
- API 602 - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS

Part No. **BCSB206F08AAB830000G**  
 (Código)  
 Description **2" Fig. 950 SW UT A105N, API TRIM No.8 830000**  
 Descripción **FORGED STEEL GATE VALVE CLASS 800**  
**(VALVULA COMPUERTA DE ACERO FORJADO CLASE 800)**  
**VALVE WITH LOW EMISSION CONTROL (50 PPMS MAX.) (VALVULA SUMINISTRADA CON CONTROL DE BAJAS EMISIONES FUGITIVAS (50 PPM'S MAX.))**

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	2975	2175	NA	NA
PNEUMATIC (PSI) (NEUMATICA)			80	80

Invoice(Factura) A35904 Item(Partida) 6  
 Qty(Cantidad) 50

#### MECHANICAL TEST (PROP. MECANICAS)

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%)											COMPOSICIÓN QUIMICA (%)					TENS	YIELD	ELG	RED	BHN
			C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	KPSI CVN@	KPSI 1ST	% 2ND	% 3RD	AVG					
BODY CUERPO	D35	ASTMA-105N	0.180	0.750	0.022	0.020	0.260	0.083	0.082	0.053	0.068	0.001							76.27	41.33	34	40	158
BODY CUERPO	D36	ASTMA-105N	0.191	0.792	0.020	0.019	0.220	0.068	0.083	0.059	0.082	0.001							77.14	40.60	39	44	158
BODY CUERPO	D38	ASTMA-105N	0.210	0.710	0.022	0.019	0.310	0.057	0.061	0.056	0.073	0.001							74.82	39.73	28	37	155
BODY CUERPO	D37	ASTMA-105N	0.190	0.760	0.019	0.017	0.250	0.082	0.077	0.063	0.074	0.001							75.84	40.75	32	39	156
YOKE YUGO	D37	ASTMA-105N	0.190	0.760	0.019	0.017	0.250	0.082	0.077	0.063	0.074	0.001							75.84	40.75	32	39	156
YOKE YUGO	D35	ASTMA-105N	0.180	0.750	0.022	0.020	0.260	0.083	0.082	0.053	0.068	0.001							76.27	41.33	34	40	158

FAC10-21 REV '3'

CERTIFICADO POR:  
 ASEGURAMIENTO DE

CERTIFIED BY:  
 QUALITY ASSURANCE

Yolanda Ponciano



Industrial de Valvulas, S.A. de C.V.  
 Av. de La Industria Lote 16 Fracc. Industrial El Trebol  
 Tepetzotlan, Estado de Mexico C.P. 54600  
 Teléfono: (52 55) 5899 1700 Fax: (52 55) 5876 0156  
 E-Mail: info@walworth.com.mx Web: www.walworthvalves.com

(Numero) Number  
 (Fecha) Date

3708/2013  
 22/10/2013

**QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE**

(ACCORDING TO EN10204 TYPE 3.1)

**ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO**

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION:

(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICIÓN.)

- |              |   |             |   |
|--------------|---|-------------|---|
| API 598      | - VALVE INSPECTION AND TESTING                      | API 6D      | - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK                                    |
| API 599      | - METAL PLUG VALVES - FLANGED, THREADED AND WELDING | API 600     | - STEEL GATE VALVES, FLANGED AND WELDING ENDS                                     |
| ANSI B 16-10 | - FACE TO FACE AND END TO END DIMENSIONS OF VALVES  | ANSI B16-11 | - FORGED FITTINGS, SOCKET - WELDING AND THREADED                                  |
| ANSI B 16-34 | - VALVES - FLANGED, THREADED AND WELDING ENDS       | API 602     | - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS |
| MSS-SP61     | - PRESSURE TESTING OF STEEL VALVES                  |             |   |

Part No. **BCSB206F08AAB830000G**  
 (Código)

Description **2" Fig. 950 SW UT A105N, API TRIM No.8 830000**

FORGED STEEL GATE VALVE CLASS 800  
 (VALVULA COMPUERTA DE ACERO FORJADO CLASE 800)

VALVE WITH LOW EMISSION CONTROL (50 PPM'S MAX.) (VALVULA SUMINISTRADA CON CONTROL DE BAJAS EMISIONES FUGITIVAS (50 PPM'S MAX.))

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	2975	2175	NA	NA
PNEUMATIC (PSI) (NEUMATICA)			80	80

Invoice(Factura) A35904 Item(Partida) 6  
 Qty(Cantidad) 50

**MECHANICAL TEST (PROP. MECANICAS)**

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%)											MECHANICAL TEST				
			C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	TENS KPSI CVN@	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD	BHN AVG
YOKE YUGO	D38	ASTM A-105N	0.210	0.710	0.022	0.019	0.310	0.057	0.061	0.056	0.073	0.001	74.82	39.73	28	37	155	
YOKE YUGO	D36	ASTM A-105N	0.191	0.792	0.020	0.019	0.220	0.068	0.083	0.059	0.082	0.001	77.14	40.60	39	44	158	

FAC10-21 REV "3"

CERTIFICADO POR:  
 ASEGURAMIENTO DE

CERTIFIED BY:  
 QUALITY ASSURANCE

Yolanda Ponciano