検査証明書
INSPECTION CERTIFICATE

JFE スチール 株式会社 東日本製鉄所(京浜地区)
JFE Steel Corporation East Japan Works(Keihin)

JFE

需要家 Customer :MARUBENI-ITOCHU STEEL MEXICO S.A. DE C.V.
需要家管理番号 Customer's Control No. :
注文者 Shipper :MARUBENI-ITOCHU STEEL INC.
注文者照合番号 Reference No. :BJE7 -YX11141Z
品名 Commodity & :HOT ROLLED STEEL PLATE
規格 Specification :ASTM A36 2014

証明書番号 Certificate No. :161220-ASHEX-8611-001 CONTINUED
日付 Date :2016-12-20
船番 Ship No. :
工事番号 Construction No. :
注文番号 Order No. :6E14882

#1 製品番号 Roll No. / 鋼番 Heat No.	行番 Item No.	需要家管理番号 Customer's Control No. / 寸法 Size T X W X L	員数 Quantity	質量 Mass (CAL)	化学成分 Chemical Composition (%) C ×100	Si	Mn	P ×1000	S	V	Nb	Cu	Ni	Mo	Cr ×100	×1000	×10	×100	引張試験 Tensile Test 降伏点/耐力 Y.P./Y.S. #4 KSI	引張強さ T.S.	伸び El #5 %	降伏比 YR %	曲げ BT	UST
SPECIFIED VALUE (STANDARD) LADLE :				MIN.															36	58	18			
				MAX.															80					
				MIN.	-	-		-	-															
				MAX.	25	40		30	30															
MK19801 11264	008	1/2" X 8' X 20'	1	1482	13	18	87	13	5			0 1	0 1	1	3				TC	42.5	64.1	32	H	
MK19802 11264	008	1/2" X 8' X 20'	1	1482																				
MK19803 11264	008	1/2" X 8' X 20'	1	1482																				
MK19804 11264	008	1/2" X 8' X 20'	1	1482																				
MK19805 11264	008	1/2" X 8' X 20'	1	1482																				
MK19806 11264	008	1/2" X 8' X 20'	1	1482																				
MK19807 11264	008	1/2" X 8' X 20'	1	1482																				
MK19808 11264	008	1/2" X 8' X 20'	1	1482																				

(注) (Notes)
#1 厚板製品番号の表示方法, Indication of Plate Roll Number
;上5桁:圧延番号, 2 letters&the 1st 3 figures:mother Plate Numbers
;下2桁:分割番号, the last 2 figures:divided Plate Numbers
#2 DG:脱ガス, Degassed

#4 位置, Position
T:頭部, Top M:中部, Middle
B:底部, Bottom
方向, Direction
L:縦, Longitudinal
C:横, Transverse
Z:厚, Through-thickness

衝撃試験片寸法, Size of Impact Test Specimen
1:10×10mm 2:7.5×10mm 3:2/3×10mm 4:5×10mm
5:1/3×10mm 6:2.5×10mm 7:Thickness×10mm
衝撃試験片特性単位, Unit of Impact Test Property
吸収エネルギー, Absorbed Energy:K:kgf.m, C:kgf.m/cm², J:Joule, U:J/cm², F:ft.lbf, L:ft.lbf/cm²
破面率, Fracture; S:延性, Shear B:脆性, Brittle
横膨出量, Lateral Expansion; M:mm I:mil

#5 標点距離, Gauge Length
A:200mm (■) D:50mm (■)
E:50mm (●) H:8" (■)
J:2" (●) K:5D (●)
M:5.65√A (●) P:5.65√A (■)
R:4D (●) S:80mm (■)
U:100mm (■) Y:2" (■)
T:70mm (●)

#6 BT :曲げ試験, Bend Test
UST:超音波探傷, Ultrasonic Examination
G :合格, Good

上記商品は検査の結果指定の規格に合格していることを証明いたします。

WE HEREBY CERTIFY THAT THE MATERIAL DESCRIBED HEREIN HAS BEEN TESTED AND INSPECTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE SPECIFICATION.

(BB4589001IBA)
S726 X A0Y

東日本製鉄所(京浜地区):〒210-0868神奈川県川崎市川崎区扇島1番地1 East Japan Works(Keihin):1-1, OHGISHIMA, KAWASAKI 210-0868 JAPAN

T. Yamazaki

東日本製鉄所(京浜地区)品質保証室
Quality Assurance Section
East Japan Works(Keihin)

This Inspection Certificate is printed with special forgery proof technology.
このミルシートは特殊偽造防止技術を使用しております