検査証明書
INSPECTION CERTIFICATE

JFE スチール 株式会社 東日本製鉄所(京浜地区)
JFE Steel Corporation East Japan Works(Keihin)
JFE

需要家 Customer :MARUBENI-ITOCHU STEEL MEXICO S.A. DE C.V.
需要家管理番号 Customer's Control No. :
注文者 Shipper :MARUBENI-ITOCHU STEEL INC.
注文者照合番号 Reference No. :BJE7 -YX106209
品名 Commodity & 規格 Specification : HOT ROLLED STEEL PLATE ASTM A36 2014

証明書番号 Certificate No. :161014-ASHEX-4422-002 CONTINUED
日付 Date :2016-10-14
船番 Ship No. :
工事番号 Construction No. :
注文番号 Order No. :6E13046

製品番号 #1 Roll No. 鋼番 Heat No.	行番 Item No.	需要家管理番号 Customer's Control No. 寸法 Size T X W X L	員数 Quantity	質量 Mass (CAL)	化学成分 Chemical Composition (%) C ×100	Si ×100	Mn ×1000	P ×1000	S ×100	V	Nb	Cu	Ni	Mo	Cr ×1000	×10	B ×100	引張試験 Tensile Test 降伏点/耐力 Y.P./Y.S. #4 KSI	引張強さ T.S.	伸び El #5 %	降伏比 YR %	曲げ BT	UST
GL33512 07389	009	1/2" X 72" X 240"	1	1112	13	20	89	26	4	0	0	1	2	1	4								
GL33514 07389	009	1/2" X 72" X 240"	1	1112														TC	42.9	64.8	32	H	
HG66102 07739	009	1/2" X 72" X 240"	1	1112	13	20	93	15	6	0	0	1	2	1	3			TC	42.1	64.5	33	H	
HG66104 07739	009	1/2" X 72" X 240"	1	1112														TC	44.5	65.3	27	H	
HG66106 07739	009	1/2" X 72" X 240"	1	1112																			
HG66108 07739	009	1/2" X 72" X 240"	1	1112																			
HG66110 07739	009	1/2" X 72" X 240"	1	1112																			
HG66112 07739	009	1/2" X 72" X 240"	1	1112																			
JC48301 07880	009	1/2" X 72" X 240"	1	1112	13	20	90	16	3	0	0	1	2	1	3			TC	41.8	65.3	29	H	
JC48302 07880	009	1/2" X 72" X 240"	1	1112														TC	40.8	65.1	30	H	
JC48303 07880	009	1/2" X 72" X 240"	1	1112																			

(注) (Notes)
#1 厚板製品番号の表示方法, Indication of Plate Roll Number
:上5桁:圧延番号, 2 letters&the 1st 3 figures:mother Plate Numbers
:下2桁:分割番号, the last 2 figures:divided Plate Numbers
#2 DG:脱ガス, Degassed

#4 位置, Position
T:頭部, Top M:中部, Middle
B:底部, Bottom
方向, Direction
L:縦, Longitudinal
C:横, Transverse
Z:厚, Through-thickness

衝撃試験片寸法, Size of Impact Test Specimen
1:10X10mm 2:7.5X10mm 3:2/3X10mm 4:5X10mm
5:1/3X10mm 6:2.5X10mm 7:ThicknessX10mm
衝撃試験値特性単位, Unit of Impact Test Property
吸収エネルギー, Absorbed Energy K:kgf.m C:kgf.m/cm² J:Joule, U:J/cm², F:ft.lbf, L:ft.lbf/cm²
破面率, Fracture; S:延性, Shear B:脆性, Brittle
横膨出量, Lateral Expansion; M:mm I:mil

#5 標点距離, Gauge Length
A:200mm(■) D:50mm(■)
E:50mm(●) H:8"(■)
J:2"(●) K:5D(●)
M:5.65√A(●) P:5.65√A(■)
R:4D(●) S:80mm(■)
U:100mm(■) Y:2"(■)
T:70mm(●)

#6 BT :曲げ試験, Bend Test
UST:超音波探傷, Ultrasonic Examination
G :合格, Good

上記商品は検査の結果指定の規格に合格していることを証明いたします。

WE HEREBY CERTIFY THAT THE MATERIAL DESCRIBED HEREIN HAS BEEN TESTED AND INSPECTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE SPECIFICATION.

(BB45890011AA)
S726 1 A08

東日本製鉄所(京浜地区):〒210-0868神奈川県川崎市川崎区扇島1番地1 East Japan Works(Keihin):1-1, OHGISHIMA, KAWASAKI 210-0868 JAPAN

T. Yamazaki
東日本製鉄所(京浜地区)品質保証室
Quality Assurance Section
East Japan Works(Keihin)

This Inspection Certificate is printed with special forgery proof technology.
—このミルシートは特殊偽造防止技術を使用しております—