

계약 번호
P/O No. : 112060

발행일자
Date of Issue : 2011. 11. 16.

증명서번호
Certificate No. : K-11-783

제품명
Commodity : ERW STEEL STRUCTURAL TUBING


제품규격
Spec. & Type : ASTM A 500 Gr.B

검사증명서

INSPECTION CERTIFICATE

수요자
Customer : FORTACERO S.A. DE C.V.

주문자
Shipper :



* Head Office : Rm 405 Woo Chang Bldg 152-2
Kamjon-dong, Sasang-gu, Busan, Korea

* Gwangyang Factory : 1653-12, Taein-dong,
Gwangyang City, Jeonnam-do, Korea

* Busan Factory : 1516-5, Dadae-dong,
Saha-gu, Busan, Korea

* Seoul Office : 507-1, Sihwa Industrial Complex 2ma,
Jungwang-dong, Siheung City, Gyeonggi, Korea

치수 Size (inch)	두께 Thick- ness (inch)	길이 Length (ft)	제품번호 Product No. (Lot No.)	수량 Quan- tity	총길이 Total Length (ft)	인장 시험 Tensile Test (Min.)			굽힘시험 Bending Test	편평시험 Flattening Test	표면상태 Surface Treatment	화학 성분(%) Chemical Composition (Max.)					제강번호 Heat No. (Coil No.)	비고 Remarks
						Y.P	T.S	E.L				C	Si	Mn	P	S		
						(MPa)	(%)	(%)				0.300	-	-	0.045	0.045		
6 x 6	0.188	40	J1J13G1AF034	549	21,960	336	446	26	-	Good	Oiled	0.1722	0.014	0.314	0.0116	0.0027	SR72201	
6 x 6	0.250	40	J1J12G1AF061	396	15,840	348	469	25	-	Good	Oiled	0.1723	0.018	0.310	0.0144	0.0026	SR72349	
8 x 4	0.188	40	J1J18G1AF043	180	7,200	336	446	26	-	Good	Oiled	0.1722	0.014	0.314	0.0116	0.0027	SR72201	
8 x 4	0.188	40	J1J18G2AF009	10	400	336	446	26	-	Good	Oiled	0.1722	0.014	0.314	0.0116	0.0027	SR72201	
8 x 4	0.375	40	J1J18G2AF023	6	240	336	458	24	-	Good	Oiled	0.1787	0.017	0.305	0.0167	0.0025	SR72347	
8 x 4	0.375	40	J1J18G2AF018	36	1,440	336	458	24	-	Good	Oiled	0.1787	0.017	0.305	0.0157	0.0025	SR72347	
8 x 6	0.375	40	J1J27G1AF020	36	1,440	336	458	24	-	Good	Oiled	0.1787	0.017	0.305	0.0157	0.0025	SR72347	
8 x 8	0.188	40	J1J24G1AQ027	216	8,640	336	446	26	-	Good	Oiled	0.1722	0.014	0.314	0.0116	0.0027	SR72201	
8 x 8	0.250	40	J1J24G1AF040	186	7,440	348	469	25	-	Good	Oiled	0.1723	0.018	0.310	0.0144	0.0026	SR72349	
8 x 8	0.375	40	J1J21G2AF020	1	40	336	458	24	-	Good	Oiled	0.1787	0.017	0.305	0.0157	0.0025	SR72347	
8 x 8	0.375	40	J1J21G1AF006	180	7,200	336	458	24	-	Good	Oiled	0.1787	0.017	0.305	0.0157	0.0025	SR72347	
10 x 6	0.188	40	J1J24G2AQ001	90	3,600	336	446	26	-	Good	Oiled	0.1722	0.014	0.314	0.0116	0.0027	SR72201	
10 x 6	0.250	40	J1J24G2AQ036	1	40	348	469	25	-	Good	Oiled	0.1723	0.018	0.310	0.0144	0.0026	SR72349	
10 x 6	0.250	40	J1J24G2AQ021	66	2,640	348	469	25	-	Good	Oiled	0.1723	0.018	0.310	0.0144	0.0026	SR72349	
*** B L A N K ***																		

Surveyor To:

본 제품은 관련 규격의 시험을 행하여 합격하였음을 증명합니다.
We hereby certify that the material has been made in accordance with the order and specification.

Manager of material testing section Ha J. S.