CERTIFICATE NO(성적서 번호) : C501090 Page 1 of 1
DATE OF ISSUE(발행일자) : 2018-05-08
CONTRACT(P/O) NO.(계약번호) : 26550
PR NO.(주문서번호) : F180200166
COMMODITY(제품명) : E.R.W. CARBON STEEL PIPE
SPECIFICATION(제품규격) : ASTM A53 B

검사증명서
MILL TEST CERTIFICATE
EN 10204 TYPE 3.1 - 2004

CUSTOMER(고객사): 현대종합상사(주)

HYUNDAI STEEL
울산공장 : 울산광역시 북구 염포로 706
706, Yeompo-ro, Buk-gu, Ulsan, Korea

No.	TYPE OF PIPE END ※1	SIZE OUT-DIA×THICK×LENGTH (외경×두께×길이)	PCS (본)	WEIGHT (KG)	TOTAL LENGTH (M)	HEAT No.	Hydrostatic Test Pressure (PSI)	Hydrostatic Test Time (SEC)	Spec.	※2	Tensile Properties(Gage Length : 2 inch) Tensile Strength Base (MPa)	Tensile Strength Weld (MPa)	Yield Strength (MPa)	Y/R Rate (%)	E.L (%)	Hardness Test ※3 Max. Value	※2 ※3	Hardness Test & CVN Impact Test CVN Impact Test(℃) Absorbed Energy(Joule) 1	2	3	avg	Shear Area (%)	D.W.T Test(℃) Shear Area(%) 1	2	avg
									Min.		415	415	240				Specimen size								
									Max.									Criteria : In the case of 10×10							
1	EB BE	10" X 0.365 " X 6.150 M	10	3,708	61.5	G75929	1430	5		T	484	531	346		38										
2	EB BE	10" X 0.365 " X 6.150 M	36	13,348	221.4	SU09235	1430	5		T	476	510	332		39										
		TOTAL	46	17,056	282.9																				

No.	Heat No.	Spec.	※4	Chemical Composition(%) C	Si	Mn ※7	P	S	Cu	Ni	Cr	Mo	V	CM3 ※10	2:×100 3:×1000 4:×10000	Zn-Coating Test Zn Coating	Copper Sulfate Test Time	Copper Sulfate Test Result	HC-Test Collapse Pressure	H.I.C Test CLR	CTR	CSR	S.S.C.C Test
		Min.		2	2	2	3	3	2	2	2	3	3	3					psi	%	%	%	
		Max.		30		120	50	45	40	40	40	150	80	1000									
1	G75929		H	17	2	65	17	5															
			P	17	2	64	18	6	5	2	4	2	2	109									
			P	17	2	64	17	5	5	2	4	2	2	109									
2	SU09235		H	18	1	48	14	3															
			P	18	1	48	11	3	3	1	3	2	1	85									
			P	18	1	47	11	3	3	1	3	2	1	83									

Heat Treatment	Non-Destructive Test (U.T)	Flattening / Bending Test	Visual & Dimension
GOOD	GOOD	GOOD	GOOD

Remark
※1) Type of pipe end(관종)
EB:ERW Black BE:Bevel End
※2) L: Longitudinal, T: Transverse
※3) B: Base, W: Weld Line, H: Heat Affected Zone
※4) H: Heat(Ladle) Analysis, P: Product Analysis
※7) For each reduction of 0.01% below the specified C max.
an increase of 0.06% Mn above the specified max.
will be permitted up to a max. of 1.65%
※10) CM3=Cu+Ni+Cr+Mo+V
※ SPEC YEAR - ASTM A53(2012ED)

SURVEYOR

본 제품은 관련 규격에 합격되었음을 보증합니다.
WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HEREIN HAS BEEN ACCEPTED IN ACCORDANCE WITH THE PRESCRIBED SPECIFICATION AND ORDER.
* 본 검사증명서에 명기된 규격용도외 사용시 안전상 문제가 발생할 수 있으며, 검사증명서 위.변조시 사문서 위조로 불이익을 당하실 수 있습니다.

T. h. Lim
QA Manager

* 본 검사증명서는 원본인 전자문서(전자서명 정보 포함)로부터 출력된 사본입니다. 전자문서의 내용은 현대제철 고객포탈에서 확인하실 수 있습니다.(http://sm.hyundai-steel.com/cs/cm/login.jsp)
* This Mill Test Certificate is a copy that has been printed from original electronic document(with digital signing).
You are able to check an original electronic document at hyundaisteel's customer portal.(http://sm.hyundai-steel.com/cs/cm/login.jsp) * QRcode scanner App : 'QReal'