CERTIFICATE NO(성적서 번호) : C501619
DATE OF ISSUE(발행일자) : 2018-05-10
CONTRACT(P/O) NO.(계약번호) : 26550
PR NO.(주문서번호) : F180200166
COMMODITY(제품명) : E.R.W. CARBON STEEL PIPE
SPECIFICATION(제품규격) : ASTM A53 B



# 검사증명서
# MILL TEST CERTIFICATE
## EN 10204 TYPE 3.1 - 2004

HYUNDAI STEEL
울산공장 : 울산광역시 북구 염포로 706
706, Yeompo-ro, Buk-gu, Ulsan, Korea

CUSTOMER(고객사): 현대종합상사(주)

| No. | TYPE OF PIPE END ※1 | SIZE OUT-DIA×THICK×LENGTH (외경×두께×길이) | PCS (본) | WEIGHT (KG) | TOTAL LENGTH (M) | HEAT No. | Hydrostatic Test Pressure (PSI) | Hydrostatic Test Time (SEC) | Spec. Min. / Max. | ※2 | Tensile Strength Base (MPa) | Tensile Strength Weld (MPa) | Yield Strength (MPa) | Y/R Rate (%) | El. (%) | Hardness Test ※3 | Hardness Test Max. Value | Hardness Test & CVN Impact Test ※2 ※3 | Specimen size | CVN Impact Test(℃) Absorbed Energy(Joule) 1 | 2 | 3 | avg | Shear Area (%) | D.W.T Test(℃) Shear Area(%) 1 | 2 | avg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | Min. | | 415 | 415 | 240 | | 26 | | | | | | | | | | | | |
| | | | | | | | | | Max. | | | | | | | | | | | Criteria : In the case of 10×10 | | | | | | | |
| 1 | EB BE | 20" X 0.250 " X 6.150 M | 57 | 27,536 | 350.55 | SP08773 | 520 | 5 | | T | 468 | 464 | 273 | | 39 | | | | | | | | | | | | |
| | | TOTAL | 57 | 27,536 | 350.55 | | | | | | | | | | | | | | | | | | | | | | |

| No. | Heat No. | Spec. | ※4 | C | Si | Mn ※7 | P | S | Cu | Ni | Cr | Mo | V | CM3 ※10 | Zn Coating | Copper Sulfate Test Time | Copper Sulfate Test Result | HC-Test Collapse Pressure (psi) | H.I.C Test CLR (%) | CTR (%) | CSR (%) | S.S.C.C Test |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | Chemical Composition(%) 2:×100 3:×1000 4:×10000 | | | | | | | | | | | Zn-Coating Test | | | | | | | |
| | | | | 2 | 2 | 2 | 3 | 3 | 2 | 2 | 2 | 3 | 3 | 3 | | | | | | | | |
| | | Min. | | | | | | | | | | | | | | | | | | | | |
| | | Max. | | 30 | | 120 | 50 | 45 | 40 | 40 | 40 | 150 | 80 | 1000 | | | | | | | | |
| 1 | SP08773 | | H | 17 | 1 | 48 | 11 | 4 | | | | | | | | | | | | | | |
| | | | P | 19 | 1 | 49 | 11 | 5 | 2 | 1 | 2 | 1 | 1 | 50 | | | | | | | | |
| | | | P | 19 | 1 | 48 | 10 | 4 | 2 | 1 | 2 | 1 | 1 | 49 | | | | | | | | |

Remark
※1) Type of pipe end(관종)
EB:ERW Black BE:Bevel End
※2) L: Longitudinal, T: Transverse
※3) B: Base, W: Weld Line, H: Heat Affected Zone
※4) H: Heat(Ladle) Analysis, P: Product Analysis
※7) For each reduction of 0.01% below the specified C max.
an increase of 0.06% Mn above the specified max.
will be permitted up to a max. of 1.65%
※10) CM3=Cu+Ni+Cr+Mo+V
※ SPEC YEAR - ASTM A53(2012ED)

| Heat Treatment | Non-Destructive Test (U.T) | Flattening / Bending Test | Visual & Dimension |
|---|---|---|---|
| GOOD | GOOD | GOOD | GOOD |

SURVEYOR

본 제품은 관련 규격에 합격되었음을 보증합니다.
WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HEREIN HAS BEEN ACCEPTED IN ACCORDANCE WITH THE PRESCRIBED SPECIFICATION AND ORDER.
* 본 검사증명서에 명기된 규격용도외 사용시 안전상 문제가 발생할 수 있으며, 검사증명서 위.변조시 사문서 위조로 불이익을 당하실 수 있습니다.

T. h. lim
QA Manager

* 본 검사증명서는 원본인 전자문서(전자서명 정보 포함)로부터 출력된 사본입니다. 전자문서의 내용은 현대제철 고객포탈에서 확인하실 수 있습니다.(http://sm.hyundai-steel.com/cs/cm/login.jsp)
* This Mill Test Certificate is a copy that has been printed from original electronic document(with digital signing).
You are able to check an original electronic document at hyundaisteel's customer portal.( http://sm.hyundai-steel.com/cs/cm/login.jsp) * QRcode scanner App : 'QReal'