CERTIFICATE NO(성적서 번호) : CB04349
DATE OF ISSUE(발행일자) : 2018-11-20
CONTRACT(P/O) NO.(계약번호) : 27377
PR NO.(주문서번호) : F180900121
COMMODITY(제품명) : E.R.W. CARBON STEEL PIPE
SPECIFICATION(제품규격) : ASTM A53 B

검사증명서
MILL TEST CERTIFICATE
EN 10204 TYPE 3.1 - 2004

HYUNDAI STEEL
울산공장 : 울산광역시 북구 염포로 706
706, Yeompo-ro, Buk-gu, Ulsan, Korea

CUSTOMER(고객사): 현대종합상사(주)

No.	TYPE OF PIPE END ※1	SIZE OUT-DIA×THICK×LENGTH (외경×두께×길이)	PCS (본)	WEIGHT (KG)	TOTAL LENGTH (M)	HEAT No.	Hydrostatic Test Pressure PSI	Hydrostatic Test Time SEC	Spec. Min. / Max.	※2	Tensile Properties(Gage Length : 2 inch) Tensile Strength Base MPa	Tensile Strength Weld MPa	Yield Strength MPa	Y/R Rate %	E.L %	Hardness Test ※3	Hardness Test Max. Value	Hardness Test & CVN Impact Test ※2 ※3 Specimen size	CVN Impact Test(℃) Absorbed Energy(Joule) 1	2	3	avg	Shear Area (%)	D.W.T Test(℃) Shear Area(%) 1	2	avg
									Min.		415	415	240													
									Max.										Criteria : In the case of 10×10)							
1	EB BE	18" X 0.375 " X 6.150 M	2	1,293	12.3	8422629	880	5		T	533	546	372		35											
2	EB BE	18" X 0.375 " X 6.150 M	10	6,464	61.5	8752119	880	5		T	542	537	382		36											
		TOTAL	12	7,757	73.8																					

No.	Heat No.	Spec.	※4	C	Si	Mn ※7	P	S	Cu	Ni	Cr	Mo	V	CM3 ※10	Zn Coating	Copper Sulfate Test Time	Copper Sulfate Test Result	HC-Test Collapse Pressure	H.I.C Test CLR	CTR	CSR	S.S.C.C Test
				2	2	2	3	3	2	2	2	3	3	3				psi	%	%	%	
		Min.																				
		Max.		30		120	50	45	40	40	40	150	80	1000								
1	8422629		H	18	2	63	15	3														
			P	17	2	63	13	2	1	1	2	1	1	48								
			P	17	2	64	12	2	1	1	2	1	1	48								
2	8752119		H	18	1	62	19	3														
			P	16	2	64	17	2	1	1	2	TR	1	40								
			P	17	2	64	16	1	1	1	2	TR	1	39								

2 :×100 3 :×1000 4 :×10000

Remark
※1) Type of pipe end(관종)
EB:ERW Black BE:Bevel End
※2) L: Longitudinal, T: Transverse
※3) B: Base, W: Weld Line, H: Heat Affected Zone
※4) H: Heat(Ladle) Analysis, P: Product Analysis
※7) For each reduction of 0.01% below the specified C max. an increase of 0.06% Mn above the specified max. will be permitted up to a max. of 1.65%
※10) CM3=Cu+Ni+Cr+Mo+V
※ SPEC YEAR - ASTM A53(2012ED)

COPY

Heat Treatment	Non-Destructive Test (U.T)	Flattening / Bending Test	Visual & Dimension
GOOD	GOOD	GOOD	GOOD

SURVEYOR

본 제품은 관련 규격에 합격되었음을 보증합니다.
WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HEREIN HAS BEEN ACCEPTED IN ACCORDANCE WITH THE PRESCRIBED SPECIFICATION AND ORDER.
* 본 검사증명서에 명기된 규격용도외 사용시 안전상 문제가 발생할 수 있으며, 검사증명서 위.변조시 사문서 위조로 불이익을 당하실 수 있습니다.

T. h. lim
QA Manager

* 본 검사증명서는 원본인 전자문서(전자서명 정보 포함)로부터 출력된 사본입니다. 전자문서의 내용은 현대제철 고객포탈에서 확인하실 수 있습니다.(http://sm.hyundai-steel.com/cs/cm/login.jsp)
* This Mill Test Certificate is a copy that has been printed from original electronic document(with digital signing).
You are able to check an original electronic document at hyundaisteel's customer portal.(http://sm.hyundai-steel.com/cs/cm/login.jsp) * QRcode scanner App : 'QReal'