CERTIFICATE NO(성적서 번호) : CA05459
DATE OF ISSUE(발행일자) : 2018-10-24
CONTRACT(P/O) NO.(계약번호) : 27377
PR NO.(주문서번호) : F180900121
COMMODITY(제품명) : E.R.W. CARBON STEEL PIPE
SPECIFICATION(제품규격) : ASTM A53 B

검사증명서
MILL TEST CERTIFICATE
EN 10204 TYPE 3.1 - 2004

CUSTOMER(고객사): 현대종합상사(주)

HYUNDAI STEEL
울산공장 : 울산광역시 북구 염포로 706
706, Yeompo-ro, Buk-gu, Ulsan, Korea

No.	TYPE OF PIPE END ※1	SIZE OUT-DIA×THICK×LENGTH (외경×두께×길이)	PCS (본)	WEIGHT (KG)	TOTAL LENGTH (M)	HEAT No.	Hydrostatic Test Pressure PSI	Hydrostatic Test Time SEC	Spec. Min. Max.	※2	Tensile Strength Base MPa	Tensile Strength Weld MPa	Yield Strength MPa	Y/R Rate %	E.L %	※3	Hardness Test Max. Value	※2 ※3	Hardness Test & CVN Impact Test: Specimen size	CVN Impact Test(℃) Absorbed Energy(Joule) 1	2	3	avg	Shear Area (%)	D.W.T Test(℃) Shear Area(%) 1	2	avg
											415	415	240														
											Criteria : In the case of 10×10)																
1	EB BE	20" X 0.250 " X 6.150 M	41	19,806	252.15	P71275	520	5		T	467	462	350		41												
2	EB BE	20" X 0.250 " X 6.150 M	2	967	12.3	P81305	520	5		T	505	484	393		36												
		TOTAL	43	20,773	264.45																						

No.	Heat No.	Spec.	※4	C	Si	Mn ※7	P	S	Cu	Ni	Cr	Mo	V	CM3 ※10	Zn Coating	Copper Sulfate Test Time	Copper Sulfate Test Result	HC-Test Collapse Pressure psi	H.I.C Test CLR %	CTR %	CSR %	S.S.C.C Test
				Chemical Composition(%) 2 :×100 3 :×1000 4 :×10000											Zn-Coating Test			HC-Test	H.I.C Test			
				2	2	2	3	3	2	2	2	3	3	3								
		Min.																				
		Max.		30		120	50	45	40	40	40	150	80	1000								
1	P71275		H	6	1	77	13	5														
			P	6	1	79	15	7	2	1	3	5	3	64								
			P	6	1	79	16	7	2	1	3	6	3	64								
2	P81305		H	6	15	103	13	2														
			P	9	18	96	14	2	2	3	3	10	2	96								
			P	9	18	96	13	2	2	3	3	10	2	97								

Remark

※1) Type of pipe end(관종)
EB:ERW Black BE:Bevel End
※2) L: Longitudinal, T: Transverse
※3) B: Base, W: Weld Line, H: Heat Affected Zone
※4) H: Heat(Ladle) Analysis, P: Product Analysis
※7) For each reduction of 0.01% below the specified C max. an increase of 0.06% Mn above the specified max. will be permitted up to a max. of 1.65%
※10) CM3=Cu+Ni+Cr+Mo+V
※ SPEC YEAR - ASTM A53(2012ED)

COPY

Heat Treatment	Non-Destructive Test (U.T)	Flattening / Bending Test	Visual & Dimension
GOOD	GOOD	GOOD	GOOD

본 제품은 관련 규격에 합격되었음을 보증합니다.
WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HEREIN HAS BEEN ACCEPTED IN ACCORDANCE WITH THE PRESCRIBED SPECIFICATION AND ORDER.
* 본 검사증명서에 명기된 규격용도외 사용시 안전상 문제가 발생할 수 있으며, 검사증명서 위.변조시 사문서 위조로 불이익을 당하실 수 있습니다.

SURVEYOR

T. H. Lim
QA Manager

* 본 검사증명서는 원본인 전자문서(전자서명 정보 포함)로부터 출력된 사본입니다. 전자문서의 내용은 현대제철 고객포탈에서 확인하실 수 있습니다.(http://sm.hyundai-steel.com/cs/cm/login.jsp)
* This Mill Test Certificate is a copy that has been printed from original electronic document(with digital signing).
You are able to check an original electronic document at hyundaisteel's customer portal.(http://sm.hyundai-steel.com/cs/cm/login.jsp) * QRcode scanner App : 'QReal'