

RG Steel, LLC
 QUALITY & CUSTOMER TECHNICAL SERVICES
REPORT OF TEST AND ANALYSIS

| | | |
|--------------------------------------------------------------------------------------------------|---------------------------------|----------------------------------|
| REQ. JOB CONTRACT NO. | PURCHASE ORDER DATE 09/23/11 | PURCHASE ORDER NO. 1003018706 |
| VENDOR RG STEEL SPARROWS POINT, LLC SPARROWS POINT PLANT SPARROWS POINT, MARYLAND 21219 | SHIPMENT NO. 406-20342 | MILL ORDER NO. 99621423 |
| | INVOICE NO. 406-20342 | |
| VEHICLE IDENTIFICATION | | DATE SHIPPED 12/28/11 |

| | |
|--------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| SOLD TO DUFERCO STEEL INC 100 MATAWAN RD - SUITE 400 MATAWAN NJ 07747 | SHIP TO DUFERCO STEEL INC C/O PENNWOOD WHARF SPARROWS POINT MD 21219 |
|--------------------------------------------------------------------------------|-------------------------------------------------------------------------------|

| | | | | | |
|---------------------------|--------------------|-----------|----------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SPECIFICATION DESCRIPTION | THICKNESS .0299 | TYPE A | WIDTH 48.00 | LENGTH | STEEL CHAR: COLD ROLLED-CLASS 1 COMMERCIAL STEEL LIGHTLY OIL LIGHT MATTE FINISH COILS SPEC CODE : ASTM A1008-LATEST REVISION CS TYPE B MOD SAE J403-LATEST REVISION 1008 |
|---------------------------|--------------------|-----------|----------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

| NOTES | PIECES | CEV | ACTUAL WEIGHT | COIL/LIFT SERIAL NO. | HEAT NUMBER and/or TEST IDENTIFICATION | YIELD | TENSILE STRENGTH | ELONG | | BEND | |
|-------|--------|-----|---------------|----------------------|----------------------------------------|-------|------------------|-------|---|------|-------|
| | | | | | | | | In. | % | | |
| | 1 | | 21660 | M84367J | 411X5271 | | | | | | 9825K |
| | 1 | | 21630 | M84367K | 411X5271 | | | | | | 9811K |
| | 1 | | 20970 | M84368J | 411X5601 | | | | | | 9512K |
| | 1 | | 20980 | M84368K | 411X5601 | | | | | | 9517K |
| | 1 | | 21160 | M84369J | 411X5602 | | | | | | 9598K |
| | 1 | | 21240 | M84369K | 411X5602 | | | | | | 9634K |
| | 1 | | 20190 | M84370J | 411X5601 | | | | | | 9158K |
| | 1 | | 21130 | M84370K | 411X5601 | | | | | | 9585K |
| | 1 | | 20810 | M84371J | 411X5601 | | | | | | 9439K |
| | 1 | | 20898 | M84371K | 411X5601 | | | | | | 9476K |

MELTED AND MANUFACTURED IN USA

NOTES

| HEAT NUMBER | CHEMICAL ANALYSIS | | | | | | | | | | |
|-------------|-------------------|-----|------|------|------|------|------|------|------|------|------|
| | C | Mn | P | S | CU | NI | CR | MO | V | TI | CB |
| 411X5601 | .06 | .35 | .010 | .009 | .040 | 0.02 | 0.03 | .005 | .003 | .002 | .001 |
| 411X5271 | .07 | .32 | .010 | .012 | .040 | 0.02 | 0.03 | .006 | .002 | .002 | .001 |
| 411X5602 | .06 | .35 | .010 | .009 | .040 | 0.02 | 0.03 | .005 | .003 | .002 | .001 |

I certify that the above results are a true and correct copy of actual results contained in records maintained by RG Steel, LLC at Sparrows Point and are in full compliance with the requirements of the specification cited. This test report cannot be altered and must be transmitted intact with any subsequent third party test reports. If required.

Division Manager Quality Assurance

RICHARD I. HOYT

DATE
12/28/11 16:24
PAGE
2
PER