

Tube Forgings of America, Inc.

5200 NW Front Avenue

Portland, OR 97210

ISO 9001-2000 Certified

8/18/2005

**Sold To:** PLESA ANÁHUAC y CÍAS, S.A. de C.V.  
 AV. VALLE DE LAS ALAMEDAS NO. 66-A  
 TULTITLAN, EDO., MEX. C. P.54940

**TFA Sales Order :** 133086  
**Customer ID:** 38350  
**Customer PO Reference:** 103  
**Attention To:**

**Ship To:** SPECIALISTS IN TRANSIT FORWARDING  
 1801 MARKLEY MODERN INDUSTRIAL P/  
 LAREDO, TX 78041

**TFA Heat Code:** N667  
**Grade:** WPB  
**TFA Part ID:** 20007  
**Description:** 3 STD CAP  
**Quantity:** 1  
**Mill:** IPSCO  
**Mill Heat :** E4F125  
**Process:** WPB-CN3P  
**Customer Part ID:**

**Test Bar Type:** ROUND  
**Yield (PSI):** 40700  
**Tensile (PSI):** 63100  
**% Elong In 4D** 29.00  
**B.H.N. :**  
**Tensile Orientation:** TRANS

C	MN	P	S	SI	MO	CR	NI	CU	V	CB	B	TI	AL	C.E.
0.160	0.900	0.013	0.013	0.170	0.020	0.110	0.110	0.250	0.010	0.010	0.0005	0.0200	0.0130	0.36

Coupon Size:	<u>Ft. Lbs</u>	<u>% Shear</u>	<u>Lateral Expansion (Mils)</u>
Charpy V notch test at degrees F:	1:	1:	1:
Charpy Orientation:	2:	2:	2:
	3:	3:	3:
	Avg:	Avg:	

1. THESE FITTINGS WERE NORMALIZED AT 1650F AND AIR COOLED. 2. THE STARTING MATERIAL IS PLATE WHICH IS SEAMLESS. 3. THE HARDNESS DOES NOT EXCEED 197BHN PART TO PART. 4. THIS PRODUCT IS SEAMLESS.

THE MATERIAL IS MANUFACTURED TO ASTM A 234 GR WPB REV: 03. ,ALSO PER ASME SEC II SA 234 GR WPB,2001 EDITION THRU ALL ADDENDAS AT TIME OF ORDER. 2. DESIGN AND DIMENSIONS TO ASME B16.9-2003 OR MSS-SP-75-98 AS APPLICABLE BY DESIGN. 3.PER NACE MR-01-75, 2003 REVISION. OUR QUALITY SYSTEM HAS BEEN REGISTERED BY ( ABS ) TO (ISO-9001. REV: 2000), CERTIFICATE #: 30248. OUR ORGANIZATIONAL STRUCTURE AND CERTIFICATION COMPLIES WITH (EN 10204-3.1.B). OUR FITTINGS SATISFY THE MATERIAL REQUIREMENT OF (PED 97/23-EC ANNEX 1-4.3 ).



*[Signature]*  
 John Peachey, Mgr. Quality Assurance