



WALWORTH

Industrial de Válvulas, S.A. de C.V.

Av. Industria 16,
Fraccionamiento Industrial El Trébol
Tepetzotlán, Edo, de México, 54600.

No. DE SERIE :

V02C9778

FECHA :

12 JUN 02

ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES STANDARES:

- API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
- API 600 - STEEL GATE VALVES - FLANGED AND BUTT-WELDING ENDS
- API 598 - VALVE INSPECTION AND TESTING
- API 599 - METAL PLUG VALVES - FLANGED AND WELDING ENDS
- ANSI B16.10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- ANSI B16.34 - VALVES - FLANGED, THREADED, AND WELDING ENDS
- MSS-SP61 - PRESSURE TESTING OF STEEL VALVES

No. PARTE: 25785P

DESCRIPCION: 3" FIG. 5206 F UT WCB, API TRIM No. 8
CAST STEEL GATE VALVE

SPECIFICATION 83000

PRUEBAS DE PRESION	CASCO	SELLO POST.	1ER LADO	2DO LADO
HIDROSTATICA (PSI)	1125	1125	N A	N A
NEUMATICA (PSI)			80	80

PARTE	No. DE COLADA	MATERIAL (ASTM)	COMPOSICION QUIMICA											PROPIEDADES MECANICAS				
			C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	TENS	ELAST	ELG	RED	BHN
			KPSI	KPSI	%	%	%	%	%	%	%	%	%	CVN@	1ST	2ND	3RD	AVG
BODY	2977A037	A 216 WCB	0.220	0.860	0.015	0.012	0.460	0.240	0.250	0.090	0.026	0.004	83.10	48.29	26.0	54.0	163	
BONNET-COVER	0201198	A 216 WCB	0.210	0.920	0.014	0.011	0.480	0.100	0.160	0.030	0.029	0.001	78.61	48.29	24.0	54.0	156	
WEDGE-DISC-PLUG	0C	A 216 WCB	0.200	0.820	0.016	0.013	0.450	0.050	0.030	0.060	0.070	0.015	86.10	53.10	27.3	46.2	187	

Jorge Soto

CERTIFICADO POR:

ASEGURAMIENTO DE CALIDAD