

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED
 ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE
 OF THE FOLLOWING STANDARS:

- | | |
|-------------|---|
| API 6D | - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK |
| API 600 | - STEEL GATE VALVES - FLANGED AND BUTT-WELDING ENDS |
| API 598 | - VALVE INSPECTION AND TESTING |
| API 599 | - METAL PLUG VALVES - FLANGED AND WELDING ENDS |
| ANSI B16.10 | - FACE TO FACE AND END TO END DIMENSIONS OF VALVES |
| ANSI B16.34 | - VALVES - FLANGED, THREADED, AND WELDING ENDS |
| MSS-SP61 | - PRESSURE TESTING OF STEEL VALVES |

PART. No.: 25788P

 DESCRIPTION: 6" FIG. 5202 F UT WCB, API TRIM No. 8
 VALV. COMP. DE ACERO FUND.

 VALVULA SUMINISTRADA CON CONTROL DE EMISIONES
 FUGITIVAS A 50 PPM'S MAX

PRESSURE TESTS	SHELL	BACK SEAT	1ST SIDE	2ND SIDE
HYDROSTATIC (PSI)	450	450	N A	N A
PNEUMATIC (PSI)			80	80

ITEM	HEAT No.	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%)											MECHANICAL TESTS				
			C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	TENS	YIELD	ELG	RED	BHN
															KPSI	KPSI	%	%
CUERPO	3255	A 216 WCB	0.200	0.900	0.028	0.019	0.480	0.034	0.030	0.005	0.033	0.003	74.69	43.51	26.0	48.0	153	
BONETE-TAPA	1825A317	A 216 WCB	0.210	0.900	0.024	0.018	0.440	0.080	0.150	0.070	0.030	0.003	77.49	47.17	28.0	54.0	156	
CUNA-BISCO-TAPON	83958	A 217 CA15	0.100	0.980	0.017	0.015	0.820	0.041	13.200	0.016	0.038	0.002	97.17	70.19	28.0	56.0	278	

CERTIFIED BY:


 QUALITY ASSURANCE