



# WALWORTH®

Industrial de Válvulas, S.A. de C.V.  
Av. de la Industria Lote 16 Fracc. Industrial el Trébol  
Tepetzotlán, Estado de México C.P. 54600

(NUMERO) NUMBER:

V03C2915

(FECHA) DATE:

31 MAR 03

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARS:

CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES

- API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
- API 600 - STEEL GATE VALVES - FLANGED AND BUT-WELDING ENDS
- API 598 - VALVE INSPECTION AND TESTING
- API 599 - METAL PLUG VALVES - FLANGED AND WELDING ENDS
- ANSI B16.10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- ANSI B16.34 - VALVES - FLANGED, THREADED, AND WELDING ENDS
- MSS-SP61 - PRESSURE TESTING OF STEEL VALVES

PART. No.: 25783P  
(CODIGO)


DESCRIPTION: 3" FIG. S202 F UT WCB, API TRIM No. 8  
(DESCRIPCION) VALV. COMP. DE ACERO FUND.

VALVULA SUMINISTRADA CON CONTROL DE EMISIONES FUGITIVAS A 50 PPM'S MAX

| PRESSURE TESTS<br>(PRUEBAS DE PRESION) | SHELL<br>(CASCO) | BACK<br>SEAT | SIDE (LADO) |     |
|--|------------------|--------------|-------------|-----|
|  |                  |              | 1           | 2   |
| HYDROSTATIC (PSI)<br>(HIDROSTATICA)    | 450              | 450          | N A         | N A |
| PNEUMATIC (PSI)<br>(NEUMATICA)         |                  |              | 80          | 80  |

| ITEM<br>(PARTE)  | HEAT<br>No.<br>(COLADA) | MATERIAL<br>(ASTM) | CHEMICAL COMPOSITION (%)<br>(COMPOSICION QUIMICA) |       |           |       |       |       |        |       |       |       |       | MECHANICAL TESTS<br>(PROP. MECANICAS) |                      |          |          |                   |
|------------------|-------------------------|--------------------|---|-------|-----------|-------|-------|-------|--------|-------|-------|-------|-------|---------------------------------------|----------------------|----------|----------|-------------------|
|                  |                         |                    | C   | Mn    | P         | S     | SI    | Ni    | Cr     | Mo    | Cu    | V     | W     | TENS<br>KPSI<br>CVN@                  | YIELD<br>KPSI<br>1ST | ELG<br>% | RED<br>% | BHN<br>3RD<br>AVG |
|                  |                         |                    | CUERPO  | 3225  | A 216 WCB | 0.220 | 0.970 | 0.030 | 0.017  | 0.480 | 0.029 | 0.037 | 0.001 | 0.030                                 | 0.003                | 72.51    | 42.06    | 29.0              |
| BONETE-TAPA      | 3228                    | A 216 WCB          | 0.210   | 0.980 | 0.030     | 0.018 | 0.470 | 0.038 | 0.034  | 0.005 | 0.038 | 0.003 | 76.14 | 45.68                                 | 27.0                 | 52.0     | 148      |                   |
| CUNA-DISCO-TAPON | D4036                   | A 217 CA15         | 0.120   | 0.980 | 0.018     | 0.017 | 0.840 | 0.040 | 12.500 | 0.018 | 0.037 | 0.002 | 96.79 | 69.62                                 | 27.0                 | 56.0     | 282      |                   |

CERTIFIED BY:



QUALITY ASSURANCE  
CERTIFICADO POR: ASEGURAMIENTO DE CALIDAD