



Industrial de Válvulas, S.A. de C.V.

Av. Industria 16,  
Fraccionamiento Industrial El Trébol  
Tepotzotlán, Edo. de México, 54600.

SERIAL NUMBER:

V03C4152  
31 JAN 03

DATE:

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:

- API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
- API 600 - STEEL GATE VALVES - FLANGED AND BUTT-WELDING ENDS
- API 598 - VALVE INSPECTION AND TESTING
- API 599 - METAL PLUG VALVES - FLANGED AND WELDING ENDS
- ANSI B16.10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- ANSI B16.34 - VALVES - FLANGED, THREADED, AND WELDING ENDS
- MSS-SP61 - PRESSURE TESTING OF STEEL VALVES

PART. No.: 25784P

DESCRIPTION: 4" FIG. 5202 F UT WCB, API TRIN No. 8  
VALV. COMP. DE ACERO FUND.

VALVULA SUMINISTRADA CON CONTROL DE EMISIONES  
FUGITIVAS A 50 PPM'S MAX

| PRESSURE TESTS    | SHELL | BACK SEAT | 1ST SIDE | 2ND SIDE |
|-------------------|-------|-----------|----------|----------|
| HYDROSTATIC (PSI) | 450   | 450       | N A      | N A      |
| PNEUMATIC (PSI)   |       |           | 80       | 80       |

| ITEM             | HEAT No. | MATERIAL (ASTM) | CHEMICAL COMPOSITION (%) |       |       |       |       |       |        |       |       |       |       | MECHANICAL TESTS |       |      |     |     |
|------------------|----------|-----------------|--------------------------|-------|-------|-------|-------|-------|--------|-------|-------|-------|-------|------------------|-------|------|-----|-----|
|                  |          |                 | C                        | Mn    | P     | S     | SI    | NI    | Cr     | Mo    | Cu    | V     | W     | TENS             | YIELD | ELG  | RED | BHN |
|                  |          |                 | KPSI                     | KPSI  | %     | %     |       |       |        |       |       |       |       |                  |       |      |     |     |
| CUERPO           | RCL5     | A 216 WCB       | 0.190                    | 0.860 | 0.024 | 0.013 | 0.500 | 0.010 | 0.060  | 0.020 | 0.040 | 0.012 | 78.19 | 47.65            | 31.6  | 57.3 | 159 |     |
| BONETE-TAPA      | 1803A723 | A 216 WCB       | 0.200                    | 0.890 | 0.019 | 0.015 | 0.430 | 0.070 | 0.160  | 0.030 | 0.053 | 0.002 | 76.36 | 43.80            | 28.0  | 56.0 | 156 |     |
| CUNA-DISCO-TAPON | 83950    | A 217 CA15      | 0.110                    | 0.810 | 0.015 | 0.016 | 0.820 | 0.041 | 13.200 | 0.017 | 0.037 | 0.003 | 98.92 | 69.04            | 25.0  | 58.0 | 278 |     |

CERTIFIED BY:

QUALITY ASSURANCE