



# WALWORTH®

Industrial de Válvulas, S.A. de C.V.  
Av. de la Industria Lote 16 Fracc. Industrial el Trébol  
Tepotzotlán, Estado de México C.P. 54600

(NUMERO) NUMBER:

V03C5798  
30 JUN 03

(FECHA) DATE:

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

### ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:

CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES

- API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
- API 600 - STEEL GATE VALVES - FLANGED AND BUT-WELDING ENDS
- API 598 - VALVE INSPECTION AND TESTING
- API 599 - METAL PLUG VALVES - FLANGED AND WELDING ENDS
- ANSI B16.10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- ANSI B16.34 - VALVES - FLANGED, THREADED, AND WELDING ENDS
- MSS-SP61 - PRESSURE TESTING OF STEEL VALVES

PART. No.: 25780P  
(CODIGO)

DESCRIPTION: 2" FIG. 5202 F UT WCB, API TRIN No. 8  
(DESCRIPCION) VALV. COMP. DE ACERO FUND.

VALVULA SUMINISTRADA CON CONTROL DE ENISIONES FUGITIVAS A 50 PPM'S MAX

PRESSURE TESTS (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK SEAT	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	450	450	N A	N A
PNEUMATIC (PSI) (NEUMATICA)			80	80

#### MECHANICAL TESTS (PROP. MECANICAS)

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%) (COMPOSICION QUIMICA)											MECHANICAL TESTS (PROP. MECANICAS)				
			C	Mn	P	S	SI	Ni	Cr	Mo	Cu	V	W	TENS	YIELD	ELG	RED	BHN
			KPSI CVN@	KPSI 1ST	% 2ND	% 3RD	AVG											
CUERPO	3616	A 216 WCB	0.210	0.930	0.027	0.018	0.460	0.000	0.033	0.000	0.026	0.004	76.14	45.68	24.0	44.0	147	
BONETE-TAPA	3615	A 216 WCB	0.200	0.940	0.022	0.013	0.470	0.009	0.036	0.000	0.028	0.003	76.86	45.68	26.0	52.0	149	
CUNA-DISCO-TAPON	04388	A 217 CA15	0.100	0.920	0.016	0.018	0.870	0.041	12.840	0.017	0.037	0.001	99.35	76.57	26.0	43.0	280	

CERTIFIED BY:

  
QUALITY ASSURANCE

CERTIFICADO POR: ASEGURAMIENTO DE CALIDAD